

# Detailed information for: B6-30-10-85

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

[Print...](#)

[Print to Pdf...](#)

Data Sheet

Documentation

## B6-30-10-85

### General Information

Extended Product Type: B6-30-10-85

Product ID:	GJL1211001R8105
EAN:	4013614149832
Catalog Description:	B6-30-10-85 Mini Contactor 380-415V 40-450Hz

**Long Description:** The B6-30-10 mini contactor is a compact 3 pole contactor with 1 auxiliary contact and screw terminals. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the silent coil, a switch position indication and the integrated possibility for rail or wall mounting.



### Categories

Products » Low Voltage Products and Systems » Control Products » Contactors » Mini Contactors

### + Accessories

### Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

### Popular Downloads

Data Sheet, Technical Information:	<a href="#">1SBC100173C0201</a>
Dimension Diagram:	<a href="#">GJL1200436F0001</a>

### Dimensions

Product Net Width:	52.5 mm
--------------------	---------

Product Net Height:	57.5 mm
Product Net Depth:	46.5 mm
Product Net Weight:	0.175 kg

## Technical

Number of Poles:	4
Mini Contactor Type:	Mini Contactor
Rated Operational Voltage:	Auxiliary Circuit 12 ... 240 V DC Auxiliary Circuit 12 ... 500 V AC/DC Main Circuit 12 ... 690 V AC/DC Main Circuit 690 V AC
Rated Frequency (f):	Control Circuit 400 Hz Control Circuit 50 Hz Control Circuit 60 Hz Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U <sub>imp</sub> ):	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U <sub>i</sub> ):	690 V acc. to UL/CSA 600 V
Number of Main Contacts NC:	0
Number of Main Contacts NO:	3
Rated Operational Current AC-1 (I <sub>e</sub> ):	(220 / 240 V) 40 °C 20 A (220 / 240 V) 55 °C 16 A (380 / 440 V) 40 °C 20 A (380 / 440 V) 55 °C 16 A (690 V) 40 °C 6 A (690 V) 55 °C 6 A
Rated Operational Power AC-3 (P <sub>e</sub> ):	(220 / 230 / 240 V) 2.2 kW (400 V) 4 kW (400 V) Three Phase 4 kW (440 V) 4 kW (500 V) 4 kW (690 V) 3 kW
Rated Short-time Withstand Current (I <sub>cw</sub> ):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 64 A
Number of Auxiliary Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Rated Operational Current AC-15 (I <sub>e</sub> ):	(120 V) 4 A (220 / 240 V) 4 A (24 V) 4 A (380 / 400 V) 3 A (500 V) 2 A
Rated Operational Current DC-13 (I <sub>e</sub> ):	(110 V) 0.7 A (220 / 240 V) 0.4 A (24 V) 2.5 A
Conventional Free-air Thermal Current (I <sub>th</sub> ):	Main Circuit 20 A
Rated Control Circuit Voltage (U <sub>c</sub> ):	380 ... 415 V AC
Coil Operating Limits:	(acc. to IEC 60947-4-1) for AC supply 0.85 ... 1.1 x U <sub>c</sub> (at θ ≤ 55 °C)
Degree of Protection:	Auxiliary Circuit Terminals IP20 Control Circuit Terminals IP20 Main Circuit Terminals IP20
Mechanical Durability:	10000000 cycle

Minimum Switching Capacity:	17 V 5 mA
Maximum Electrical Switching Frequency:	AC-1 300 cycles per hour AC-15 600 cycles per hour AC-3 600 cycles per hour DC-1 600 cycles per hour DC-13 600 cycles per hour DC-3 600 cycles per hour
Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
Connecting Capacity Control Circuit:	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
Wire Stripping Length:	Auxiliary Circuit 9 mm Main Circuit 9 mm
Tightening Torque:	Auxiliary Circuit 0.8 ... 1.1 N·m Control Circuit 0.8 ... 1.1 N·m Main Circuit 0.8 ... 1.1 N·m
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Power Loss:	at Rated Operating Conditions per Pole 2 W
Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

## Environmental

Ambient Air Temperature:	Operation -25 ... +55 °C Storage -40 ... +80 °C
Maximum Operating Altitude Permissible:	2000 m
Resistance to Shock acc. to IEC 60068-2-27:	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6:	5g / 5 ... 150 Hz
RoHS Status:	Following EU Directive 2011/65/EC

## Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC Auxiliary Circuit 600 V AC/DC
Full Load Amps Motor Use:	(240 V AC) Single Phase 4.9 A (440 ... 480 V AC) Three Phase 4.8 A
Horsepower Rating UL/CSA:	(208 V AC) Three Phase 1 Hp (220 ... 240 V AC) Single Phase 0.5 Hp (220 ... 240 V AC) Three Phase 2 Hp (440 ... 480 V AC) Three Phase 3 Hp (550 ... 600 V AC) Three Phase 1 Hp
General Use Rating UL/CSA:	(300 V AC) 12 A
Connecting Capacity Main Circuit UL/CSA:	Stranded 1/2x 22-10 AWG

Connecting Capacity Auxiliary Circuit UL/CSA:	Stranded 1/2x 22-10 AWG
---	-------------------------

Tightening Torque UL/CSA:	Auxiliary Circuit 7 in-lb Control Circuit 7 in-lb Main Circuit 7 in-lb
---------------------------	--

## Certificates and Declarations (Document Number)

BV Certificate:	1SAA920000-0204
-----------------	-----------------

CB Certificate:	1SAA938000-2002
-----------------	-----------------

CCC Certificate:	1SAA938001-3804
------------------	-----------------

cUL Certificate:	cUL E191658
------------------	-------------

Declaration of Conformity - CE:	1SAD938512-0001
---------------------------------	-----------------

DNV GL Certificate:	1SAA938000-0306
---------------------	-----------------

EAC Certificate:	1SAA920000-2702
------------------	-----------------

Environmental Information:	1SAA938002-2401
----------------------------	-----------------

Instructions and Manuals:	2CDC102047M6801
---------------------------	-----------------

KC Certificate:	1SAA938000-1501
-----------------	-----------------

LR Certificate:	1SAA938000-0504
-----------------	-----------------

RMRS Certificate:	1SAA938000-0704
-------------------	-----------------

RoHS Information:	1SAD938512-0001
-------------------	-----------------

## Container Information

Package Level 1 Units:	10 piece
------------------------	----------

Package Level 1 Width:	115 mm
------------------------	--------

Package Level 1 Height:	54 mm
-------------------------	-------

Package Level 1 Length:	280 mm
-------------------------	--------

Package Level 1 Gross Weight:	1.82 kg
-------------------------------	---------

Package Level 1 EAN:	4013614412691
----------------------	---------------

## Classifications

Object Classification Code:	Q
-----------------------------	---

E-nummer:	3210026
-----------	---------

ETIM 4:	EC000066 - Magnet contactor, AC-switching
---------	---

ETIM 5:	EC000066 - Magnet contactor, AC-switching
---------	---

ETIM 6:	EC000066 - Power contactor, AC switching
---------	--

eClass:	7.0 27371003
---------	--------------

UNSPSC:	39121529
---------	----------

## Contact information

What would you like to do?


I need more information

ABB Sales

Submit your inquiry

Your local ABB Sales Team

Country

United States of America 

Name

Customer Support

Name

Company

E-Mail

Phone

Zip code

Your message

[→ Privacy policy](#)

Cancel

**Send message**

 Close