



NOTES:

1. MATERIALS

- HOUSING: ENGINEERING THERMOPLASTIC. COLOUR: BLACK. FLAMMABILITY RATING UL 94V-0
- CONTACTS: PHOSPHOR BRONZE
- PLATING: GOLD PLATING ON MATING AREA REFER TO THE AMPHENOL PART NO. 50 μ" [1.27 MICRONS] MIN. NICKEL UNDERPLATE 100 μ" [2.54 MICRONS] MIN. MATTE-TIN OR GOLD FLASH ON CONTACT TAILS. COPPER ALLOY PLATING: NICKEL

RECOMMENDED SOLDERING TEMPERATURE

WAVE SOLDERING PEAKED AT 265°C MAX FOR 10 SECOND MAX.

AMPHENOL PART NUMBER

RJSNE-XF8X-A8X

- GOLD PLATING: REFER TO LED OPTIONS DRAWING FOR ORDERING CODES
- D = 6u"
- G = 15u"
- J = 30u"
- 5 = 50u"

UNLESS SPECIFIED OTHERWISE	DRAWN	RONNIE.C	MAY08/18
PRIMARY UNITS: INCHES	CHECKED	AMY.Z	MAY08/18
SECONDARY: MILLIMETERS	M.E. APP'D		
	Q.A. APP'D		
	DWG APP'D		
	ENG. REL. NO.		
1 DECIMAL PLACE	REF.	EAR# RJ18096	
2 DECIMAL PLACES			
3 DECIMAL PLACES ±.015			
ANGULAR DEGREES			
	THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING

Amphenol Canada Corp. www.amphenolcanada.com			
TITLE STACKABLE MODULAR JACK, 2X4 PORTS, 8 POSITIONS, 8 CONTACTS, WITH LEDS, SHIELDED WITHOUT TABS, .130INCH CONTACT TAILS, TRAY PACKAGING -RoHS COMPLIANT			
DWG NO.		P-RJSNE-XF8X-A8X	
CODE ID NO. 03554	DWG SIZE	SCALE	SHEET 1 OF 1