

What can we help you find?



Industries About TE Products Resources My Account Innovation Support Center

Home > Products > Relays > Product Feature Selector > Product Details

7032ACC Product Details



Active

Time Delay Relays


7032ACC=RLY,STD,DBH,2P,120V,20SEC,20SEC

7032ACC (2-1423183-3)

TE Internal Number: 2-1423183-3

Product Highlights View All

- 7000 Electropneumatic Timing Industrial Series
- Input Voltage = 120 VAC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A @ 240 VAC
- Mounting Options = Mounting Bracket



Related Products

you're looking for?

View Part in Product Feature Selector

Check for Tooling

Find Similar Products

Not quite the product

Documents

Features

Compliance

Please Note:

Use the Product Drawing for all design activity

Mechanical Attachment	
Mounting Options	Mounting Bracket
Electrical Characteristics	
Input Voltage (VAC)	120
Contact Rating	10A @ 240 VAC
Termination Features	
Termination Type	Screw Terminal
Dimensions	
Approx. Dimensions (L x W x H) (mm [in])	114.80 x 65.30 x 71.90 [4.523 x 2.572 x 2.832]
Contact Features	
Delay Time	2 seconds to 20 seconds
Type of Control	Knob
Repeatability, Max.	± 15%

5
2 Form C, DPDT, 2 C/O
Without
CE Approved, CSA Certified, UL Listed
Not ELV/RoHS compliant
Not relevant for lead free process
,
-30 - +75
On/Off-Delay
7000 Electropneumatic Timing - Industrial
Agastat

Corporate Information

About TE Investors News Room Supplier Portal

Terms & Conditions

Privacy Policy

Careers

Global Accessibility Statement

Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center Site Map

Customer Support

Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account

Keep Me Informed









