

OK

OK

Panasonic

Search Keyword

**AUTOMATION
CONTROLS**



Search Site

Search Discontinued Products

Sign In / Register

[Products](#) [Downloads](#) [Learn Our Products](#) [Support](#)

[Home](#) [Business](#) > [Industrial Devices](#) > [Automation Controls Top](#) > [FP7 Input and Output units](#) > [AFP7Y32P](#)

[English \(Asia Pacific\)](#)

AFP7Y32P | FP7 Input and Output units



DOWNLOAD

[CAD data](#) [Catalogs](#) [Manuals](#) [Software](#) [HELP](#) [FAQ](#)

[Share](#) [Tweet](#) [G+](#)

Print This Page



*Photo may vary from actual product.

**RoHS
compliant**

Product Number	AFP7Y32P
Part Number	AFP7Y32P
Product	FP7 Input and Output Units
Details	Output units
Product name	FP7 Input and Output units

CONTACT US BY EMAIL

Please click your area to select country or region

- Asia-Pacific
- Middle East

BY PHONE

Singapore **+65-6390-3706**
 India **+91-124-4751300**
 Indonesia **+62-21-252-1616**
 Vietnam **+84-8-3813-4591**
 Thailand **+66-2-693-1870**
 Malaysia **+60-3-2297-6888**
 Philippines **+632-886-6291**
 Turkey **+90-216-681-0400**

[Distributors in Asia-Pacific, Middle East](#)

FAQ


RECOMMENDS

[Introduction to Automation Controls](#)



FEATURES

[A Vital Piece to the EV and HEV Puzzles](#)




[Panasonic Products for Energy Management](#)



[TOUGH for Mobiles](#)



[MID Solutions \(MIPTEC\)](#)



As of July 16, 2018
 Specifications and design of the products are subject to change without notice for the product improvement.

Spec Detail

Item	Specifications
Product Number	AFP7Y32P
Part Number	AFP7Y32P

OUTPUT SPECIFICATIONS

Item	Specifications
Insulation method	Photocoupler insulation
Rated control capacity	-
Min. load	-
Output type	Open collector
Rated load voltage	5 to 24 V DC
Load voltage allowable range	4.75 to 26.4 V DC
Max. load current:0.3 A (Y0 to Y7)	0.3 A (20.4 to 26.4 V DC), 30 mA (4.75 V DC)
Max. load current:0.1 A (other than that above)	0.3 A (20.4 to 26.4 V DC), 30 mA (4.75 V DC)
Common restriction	3.2 A/common
Max. surge current	0.6 A
OFF state leakage current	1 micro A or less
ON state maximum voltage drop	0.5 V or less
Repose time:OFF→ON	0.1 ms or less (at load current 2 mA or more)

Repose time:ON→OFF	0.5 ms or less (at load current 2 mA or more)
Life time:Mechanical life	-
Life time:Electrical life	-
External power supply:Voltage	4.75 to 26.4 V DC
External power supply:Current (at 24 V)	130 mA
Surge absorber	Zener diode
Relay socket	-
Short circuit protection	-
Output points per common	32 points/common
Operating mode indicator	32 points LED display (lights when ON)
External connection method	Connector (MIL-compliant 40 pins)

COMMON GENERAL SPECIFICATIONS




Item	Specifications
Ambient temperature	0 to +55 degrees +32 to +131 degrees Fahrenheit , at storage: -40 to +70 degrees -40 to +158 degrees Fahrenheit
Ambient humidity	10 to 95 % RH (at 25 degrees 77 degrees Fahrenheit , no condensation), at storage: 10 to 95 % RH (at 25 degrees 77 degrees Fahrenheit , no condensation)
Breakdown voltage	500 V AC for 1 minute (Note) The breakdown voltage is 2,300 V AC, 1 minute.
Insulation resistance	100 MOhm or more (at 500 V DC)
Vibration resistance	5 to 8.4 Hz, single amplitude of 3.5 mm 0.14 in, 1 sweep/min. (IEC61131-2); 8.4 to 150 Hz, constant acceleration of 9.8 m/s ² , 1 sweep/min. (IEC61131-2); for 10 min. each in X, Y, and Z directions
Shock resistance	147 m/s ² or more, 3 times each in X, Y, and Z directions (IEC61131-2)
Noise immunity	1,000 V [p-p] with pulse width 50 ns and 1 micro s (using a noise simulator)
Operating condition	Free from corrosive gasses and excessive dust

INDIVIDUAL GENERAL SPECIFICATIONS

Item	Specifications
Rated voltage range	-
Current consumption	50 mA or less
Net weight	95 g approx.

[↑ Return to top](#)

Accessories (Option)

		
Product Number AFP2801	Product Number AFP2802	Product Number AXW7221FP
Part Number AFP2801	Part Number AFP2802	Part Number AXW7221FP
Product name Discrete-wire connector set	Product name Flat cable connector set	Product Pressure contact for multi-wire
		Product name Pressure contact for multi-wire

[→ More](#)

Applicable Products

[+ Programmable Controllers / Interface Terminal](#)

CONTACT US If you have any questions, please select the option below to contact us or find answers.

[CONTACT BY EMAIL / PHONE](#)

[FIND LOCAL OFFICE](#)

[SEARCH FAQ](#)

Customer Satisfaction Survey Questionnaire

Please help us improve Panasonic Automation Controls website by completing our online survey.

We are always looking to make our website more user-friendly and comfortable for you.

We aim to use feedback positively to improve our website, please give us comments or requests you may have.

Please take a few moments to answer these questions about our website. Thank you.

Easy to understand : yes no

Easy to find the information you need : yes no

Practical for your work : yes no

[▶ Comments about our website.](#)

[Clear](#)

[Submit](#)

Customer Satisfaction Survey Questionnaire

Please help us improve Panasonic Automation Controls website by completing our online survey.

We are always looking to make our website more user-friendly and comfortable for you.

We aim to use feedback positively to improve our website, please give us comments or requests you may have.

Please take a few moments to answer these questions about our website. Thank you.

Easy to understand : yes no

Easy to find the information you need : yes no

Practical for your work : yes no

[▶ Comments about our website.](#)

[Clear](#)

[Submit](#)

[Home](#) [Business > Industrial Devices > Automation Controls Top > FP7 Input and Output units > AFP7Y32P](#)
[Business > Industrial Devices > Automation Controls Top > FP7 Input and Output units > AFP7Y32P](#)

Consumer

[Digital Cameras](#) [Digital Video Cameras](#) [Technics](#) [SD Cards](#) [Batteries](#) [Air Conditioning](#) [Telephones](#)
[Home Network System](#) [Faxes \(Drivers/Software\)](#) [Network Cameras](#) [Mobile Phones \(Software\)](#) [Video Intercom](#) [Tourist Models](#)

Business

[Communication Solutions](#) [Security Systems](#) [Personal Computer](#) [Professional AV](#) [Document & Imaging Solutions](#)
[Optical Disc Archive Solution](#) [Recording Media](#) [Video Intercom](#) [Air Conditioning](#) [Ventilation, Air Purification, etc.](#) [Photovoltaic Lighting](#) [Wiring Devices](#) [Factory Flexible wiring System](#) [Housing Equipment Devices](#) [Power Supply Solutions](#)
[Industrial Devices & Solutions](#) [Semiconductor](#) [Automation Controls](#) [Targeting ITS by Panasonic](#) [Healthcare](#)

Support

[About Us](#) [Sustainability](#) [IR](#) [News](#) [Major Exhibitions](#) [Words of Wisdom](#)

[Print](#)

[Page top](#)

[Area / Country](#)

