

OK

OK

Panasonic

Search Keyword

AUTOMATION
CONTROLS



Search Site

Search Discontinued Products

Sign In / Register

[Products](#) [Downloads](#) [Learn Our Products](#) [Support](#)

[Home](#) > [Business](#) > [Industrial Devices](#) > [Automation Controls Top](#) > [FA Sensors & Components](#) > [Sensors](#) > [Photoelectric Sensors / Laser Sensors](#)
> [Ultra-minute Photoelectric Sensor EX-Z](#) > [Part Number](#) > [EX-Z13FB](#)

[English \(Global\)](#)

EX-Z13FB | Ultra-minute Photoelectric Sensor EX-Z



DOWNLOAD

[CAD data](#) [Catalogs](#) [Manuals](#) [Software](#)




HELP

[FAQ](#)

[Share](#) [Tweet](#) [G+](#)

Print This Page



*Photo may vary from actual product.

RoHS compliant

[→ Dimensions](#)

[↓ Accessories \(Option\)](#)

Product Number	EX-Z13FB
Part Number	EX-Z13FB
Product	Ultra-minute Photoelectric Sensor
Details	Thru-beam [Front sensing]
Product name	Ultra-minute Photoelectric Sensor EX-Z

CONTACT US BY EMAIL

Please click your area to select country or region

- Europe
- Africa
- Middle East
- Asia-Pacific
- East Asia
- The Americas

BY PHONE

U.S.A. **+1-800-344-2112**
 Europe **+49-89-45354-1000**
 China **+86-10-59255988**
 Singapore **+65-6299-9181**

[→ Global Sales Network](#)

FAQ

As of July 16, 2018

Specifications and design of the products are subject to change without notice for the product improvement.

Spec Detail

Item	Specifications
Product Number	EX-Z13FB
Part Number	EX-Z13FB
CE marking directive compliance	EMC Directive, RoHS Directive
Output operation	Dark-ON
Sensing range	500 mm 19.685 in
Min. sensing object	ø1.0 mm ø0.039 in opaque object (Completely beam interrupted object)(Setting distance between emitter and receiver: 500 mm 19.685 in)
Repeatability(perpendicular to sensing axis)	0.05 mm 0.002 in or less
Supply voltage	12 to 24 V DC ±10 % Ripple P-P 10 % or less
Current consumption	Emitter: 10 mA or less Receiver: 10 mA or less
Output	NPN open-collector transistor - Maximum sink current: 20 mA - Applied voltage: 30 V DC or less (between output and 0 V) - Residual voltage: 1.5 V or less (at 20 mA sink current)
Output:Short-circuit protection	Incorporated
Response time	0.5 ms or less
Operation indicator	Orange LED (Lights up when the sensing output is ON)

RECOMMENDS

[Introduction to Automation Controls](#)



FEATURES

[A Vital Piece to the EV and HEV Puzzles](#)




[Panasonic Products for Energy Management](#)



[TOUGH for Mobiles](#)



[MID Solutions \(MIPTC\)](#)






Stability indicator	Green LED (Lights up under the stable light received condition or the stable dark condition)
Protection	IP67 (IEC)
Ambient temperature	-10 to +55 °C 14 to +131 F (No dew condensation or icing allowed), Storage: -30 to +70 °C -22 to +158 F
Ambient humidity	35 to 85 % RH, Storage: 35 to 85 % RH
Ambient illuminance	Incandescent light: 5,000 lx at the light-receiving face
Voltage withstandability	1,000 V AC for one min. between all supply terminals connected together and enclosure
Insulation resistance	20 MΩ or more, with 250 V DC megger between all supply terminals connected together and enclosure
Vibration resistance	10 to 500 Hz frequency, 3 mm 0.118 in amplitude in X, Y and Z directions for two hours each
Shock resistance	500 m/s ² acceleration (50 G approx.) in X, Y and Z directions for three times each
Emitting element	Red LED (Peak emission wavelength: 650 nm 0.026 mil , modulated)
Grounding	Floating
Material	Enclosure: PBT Lens: Polycarbonate Metallic part: Stainless steel (SUS304)(SUS301 for rear side of front sensing type)
Cable	0.1 mm ² 3-core (emitter: 2-core) cabtyre cable, 2 m 6.562 ft long Note: The bending-resistant cable type has a 0.1 mm ² 3-core (thru-beam type emitter: 2-core) bending-resistant cabtyre cable, 2 m 6.562 ft long.
Cable extension	Extension up to total 50 m 164 ft is possible with 0.3 mm ² , or more, cable (both emitter and receiver) .
Weight	Net weight (each emitter and receiver) : 15 g approx. Gross weight: 35 g approx.
Accessory	M2 mounting screws: 1 set (front sensing type: 6 mm 0.236 in in length; side sensing type: 10 mm 0.394 in in length)
Remark	Where measurement conditions have not been specified precisely, the conditions used were an ambient temperature of +23 °C 73 F .

→ [Dimensions](#)

↓ [Accessories \(Option\)](#)

↑ [Return to top](#)

Accessories (Option)

		
Product Number MS-EXZ-1	Product Number MS-EXZ-2	Product Number MS-EXZ-4
Part Number MS-EXZ-1	Part Number MS-EXZ-2	Part Number MS-EXZ-4
Product name Mounting bracket	Product name Mounting bracket	Product name Universal sensor mounting bracket

↑ [Return to top](#)

CONTACT US If you have any questions, please select the option below to contact us or find answers.

[CONTACT BY EMAIL / PHONE](#)

[FIND LOCAL OFFICE](#)

[SEARCH FAQ](#)

↑ [Return to top](#)

Customer Satisfaction Survey Questionnaire

Please help us improve Panasonic Automation Controls website by completing our online survey.

We are always looking to make our website more user-friendly and comfortable for you.

We aim to use feedback positively to improve our website, please give us comments or requests you may have.

Please take a few moments to answer these questions about our website. Thank you.

Easy to understand : yes no
Easy to find the information you need : yes no
Practical for your work : yes no

[▶ Comments about our website.](#)

Clear

Submit

Customer Satisfaction Survey Questionnaire

Please help us improve Panasonic Automation Controls website by completing our online survey.

We are always looking to make our website more user-friendly and comfortable for you.

We aim to use feedback positively to improve our website, please give us comments or requests you may have.

Please take a few moments to answer these questions about our website. Thank you.

Easy to understand : yes no
Easy to find the information you need : yes no
Practical for your work : yes no

[▶ Comments about our website.](#)

Clear

Submit

[Home](#) [Business > Industrial Devices > Automation Controls Top > FA Sensors & Components > Sensors > Photoelectric Sensors / Laser Sensors > Ultra-minute Photoelectric Sensor EX-Z > Part Number > EX-Z13FB](#)
[Business > Industrial Devices > Automation Controls Top > FA Sensors & Components > Sensors > Photoelectric Sensors / Laser Sensors > Ultra-minute Photoelectric Sensor EX-Z > Part Number > EX-Z13FB](#)

Consumer

[Digital Cameras](#) [Digital Video Cameras](#) [Technics](#) [SD Cards](#) [Batteries](#) [Air Conditioning](#) [Telephones](#)
[Home Network System](#) [Faxes \(Drivers/Software\)](#) [Network Cameras](#) [Mobile Phones \(Software\)](#) [Video Intercom](#) [Tourist Models](#)

Business

[Communication Solutions](#) [Security Systems](#) [Personal Computer](#) [Professional AV](#) [Document & Imaging Solutions](#)
[Optical Disc Archive Solution](#) [Recording Media](#) [Video Intercom](#) [Air Conditioning](#) [Ventilation, Air Purification, etc.](#) [Photovoltaic Lighting](#) [Wiring Devices](#) [Factory Flexible wiring System](#) [Housing Equipment Devices](#) [Power Supply Solutions](#)
[Industrial Devices & Solutions](#) [Semiconductor](#) [Automation Controls](#) [Targeting ITS by Panasonic](#) [Healthcare](#)

Support

[About Us](#) [Sustainability](#) [IR](#) [News](#) [Major Exhibitions](#) [Words of Wisdom](#)

 [Print](#)

[^](#)
[Page top](#)

[Area / Country](#)

Copyright © Panasonic Corporation

[Site Map](#) | [Terms of Use](#) | [Privacy Policy](#) | [Cookies Policy](#) | [Handling of personal information](#)