



BOURNS®

Features

- Surface Mount 3 mm Square / Multiturn Cermet / Industrial / Sealed
- Sealed to withstand standard board wash processing
- Pick and place centering design for automated placement compatibility
- Flush adjustment screw
- Meets EIA/EIAJ/IPC/VECI SMD standard trimmer footprint
- Top adjust

3223 - 3 mm SMD Trimming Potentiometer

Electrical Characteristics

Standard Resistance Range10 Ω to 2 MΩ
 (see standard resistance table)
 Resistance Tolerance.....±20 % std.
 Absolute Minimum Resistance
 ...1 % or 3 Ω max. (whichever is greater)
 Contact Resistance Variation
 ...3 % or 3 Ω max. (whichever is greater)
 Resolution.....Essentially infinite
 Insulation Resistance500 VDC
 100 MΩ min.
 Dielectric Strength
 Sea Level600 VAC (1 minute)
 Adjustment Angle.....11 turns nom.

Environmental Characteristics

Power Rating (200 volts max.)
 70 °C0.125 watt
 150 °C0 watt
 Temperature Range-65 °C to +150 °C
 Temperature Coefficient.....±100 ppm/°C
 HumidityMIL-STD-202 Method 106
 TRS ±3 %; IR 10 MΩ
 Vibration20 G TRS ±1 %; VRS ±1 %
 Shock100 G TRS ±1 %; VRS ±1 %
 Load Life
 @ 70 °C rated power 1000 hours
 CRV ...4 Ω or 4 % (whichever is greater)
 Rotational Cycling200 cycles
 CRV ...4 Ω or 4 % (whichever is greater)
 Thermal Shock5 cycles
 TRS ±2 %; VRS ±2 %

Physical Characteristics


Mechanical Stop.....Wiper idles
 Torque.....2.50 oz-in. max
 Weight.....Approximately 0.01 oz.
 Marking.....Manufacturer's code,
 resistance code and date code
 SolderabilityPer MIL-STD-202,
 Method 208
 WiperSet at 50 % nominal
 FlammabilityUL94V-0
 Adjustment Tool.....H-92

How To Order


3223 W - 1 - 502 E

Model _____
 Style _____
 Standard Product Indicator _____
 -1 = IR Reflow (Standard)
 Resistance Code _____
 Packaging Options _____
 E = 500 pcs./7 " Reel (Standard)
 _ = 50 pcs./tube (No suffix required)

Product Dimensions




Recommended Land Pattern



Standard Resistance Table

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
50,000	503
100,000	104
200,000	204
500,000	504
1,000,000	105
2,000,000	205

Popular values listed in boldface. Consult factory for special resistances.



Reliable Electronic Solutions

Asia-Pacific: TEL +886-2 25624117
 FAX +886-2 25624116

Europe: TEL +41-41 7685555
 FAX +41-41 7685510

N. America: TEL +1-909 781-5500
 FAX +1-909 781-5700

www.bourns.com