



Search:



Products

Catalogs

Search

Customer Support

About Cannon

Home



Plastic / Metal Coupling / Sealed

PART NUMBER: 192900-0000

<b>Product Family</b>	Trident
<b>Product Group</b>	Neptune, TNM, Multiway, Ringlock, Snap Together, Contact
<b>Component</b>	Contact
<b>Packaging</b>	Reeled (3000)
<b>Contact Finish</b>	Tin
<b>Contact Type</b>	Stamped
<b>Type of Contact</b>	Pin
<b>Wire Range mm<sup>2</sup></b>	0,50 - 1,50
<b>Wire Size</b>	20-16 AWG
<b>Contact Material</b>	Copper Alloy
<b>Contact Current Rating</b>	16 A
<b>Contact Resistance</b>	5 m ohms
<b>Mating Cycles</b>	200 Insertions
<b>Contact Retention (minimum)</b>	67 N
<b>Retention Spring Material</b>	Brass
<b>For more information</b>	Contact Cannon Sales Department
<b>Nomenclature</b>	T2P16MC4ST
<b>Insulation Diameter</b>	Ø2,00 (.078) - 3,00 (.118)
<b>Strip Length</b>	3,95 ±0,25 (.155 ±.009)
<b>Footnote</b>	Dimensions are in mm (inch). Dimensions are subject to change.

- Sales Support
- Ask a Specialist
- Product Home
- Stock Check

[Sign In](#) | [Contact Us](#) | [Legal Disclaimer](#) | [Privacy Policy](#) | [Home](#)

© 2006 ITT Industries