



121587-0015

Part Number Details

Global Mfg Part No.	121587-0015
series	TSTRECT
category	Trident
line	Trident
brand	Cannon
ittPartNo	TFR24PA10

Series	Trident Flame Retardant Rectangular
Operating Voltage	Up to 250 V ac rms
Contact Current Rating	Up to 13 A
Operating Temperature	-55°C to +105°C
Insulation Resistance	5000 Megaohms at 500 V dc
Durability	Up to 500 Mating Cycles
Flammability Rating	UL94-V0
Number of Contacts	24
Type	Free Plug
Contact Type	No Contacts delivered, please order separately.
Colour	Insulator: Grey Polyamid for Railway Applications
rohsCompliantString	material restrictions of lead, cadmium, hexavalent chromium, mercury, poly bromated biphenyl ether (PBB) and poly bromide diphenyl ether (PBDE) according to directive 2011/65/EU
rohsCompliantFlag	YES

A datasheet is available for download.

[Download Datasheet PDF](#)

Check the stock availability of this product at our distributors.

Check Stock Now

Part Number	Distributor	Qty	Location
-------------	-------------	-----	----------

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Contact Us" at the top of every page.

globalManufPartNo: 121587-0015; line: Trident; ittPartNo: TFR24PA10

[Request a Quote](#)