


<b>DRAWING NUMBER:</b>	<b>10-821-X-XX</b>
<b>PRODUCT GROUP:</b>	TERMINALS
<b>SUB-GROUP:</b>	COMMERCIAL NON-INSULATED TERMINALS
<b>DESCRIPTION:</b>	NON-INSULATED FEED THRU TERMINAL



BOARD / PANEL MOUNTING METHOD	MOUNTING HOLE SIZE	DRILL SIZE	FEED THRU COMBINATION
SWAGE MOUNT	0.094" ± 0.001	3/32"	PIN/PIN

**PART NO. STRUCTURE:**

10-821 - X - XX  
PART SERIES    DIMENSION    FINISH

**MATERIAL OPTIONS:**

10-821-X-XX

COMPONENT	MATERIAL	MATERIAL AND SPECIFICATION
TERMINAL	BRASS	BRASS PER ASTM B16, ALLOY C36000, 1/2 HARD

**DIMENSION OPTIONS:**

10-821-X-XX

DIMENSION	A	D	PIN DIAMETER	OVERALL LENGTH	SHANK LENGTH (L)	BOARD/PANEL THICKNESS
1	N/A	N/A	0.040" ± 0.005	0.408"	0.075"	1/32"
2	N/A	N/A	0.040" ± 0.005	0.438"	0.105"	1/16"
3	N/A	N/A	0.040" ± 0.005	0.468"	0.135"	3/32"
4	N/A	N/A	0.040" ± 0.005	0.498"	0.165"	1/8"

FINISH - PLATING OPTIONS:

10-821-X-**XX**

FINISH CODE	COMPONENT	FINISH	FINISH AND SPECIFICATION
01	TERMINAL	SILVER	0.000300"MIN. SILVER PER ASTM B700, TYPE 2, GRADE D WITH A NON-CHROMATE PRESERVATIVE TREATMENT
03	TERMINAL	GOLD	0.000010"MIN. GOLD PER ASTM B488, TYPE II, CODE C OVER 0.000050"MIN. NICKEL PER SAE-AMS-QQ-N-290
035	TERMINAL	GOLD	0.000050"MIN. GOLD PER ASTM B488, TYPE II, CODE C OVER 0.000050"MIN. NICKEL PER SAE-AMS-QQ-N-290
04	TERMINAL	ELECTRO-TIN	0.000300"MIN. ELECTRO-TIN PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
044	TERMINAL	BRIGHT ELECTRO-TIN	0.000300"MIN. BRIGHT ELECTRO-TIN PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
05	TERMINAL	ELECTRO-SOLDER	0.000300"MIN. ELECTRO-SOLDER PER SAE-AMS-P-81728 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
088	TERMINAL	BRIGHT TIN-LEAD	0.000300"MIN. BRIGHT TIN-LEAD (Sn93%-Pb7%) PER ASTM B545 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418
095	TERMINAL	HOT SOLDER DIP	0.000100"MIN. HOT SOLDER DIP USING Sn60 PER IPC-J-STD-006 OVER 0.000100"MIN. COPPER PER SAE-AMS-2418

TOLERANCES:\*

DECIMAL	FRACTIONAL	ANGULAR	DRAWING ORIGATION DATE	LAST MODIFICATION DATE
± 0.005	± 1/64	± 5 °	1/25/2000	3/1/2017

\*All dimensions are in inches.

RoHS COMPLIANCE:

10-821-1-XX

PART NUMBER	RoHS COMPLIANT
10-821-1-01	YES
10-821-1-03	YES
10-821-1-035	YES
10-821-1-04	YES
10-821-1-044	YES
10-821-1-05	NO
10-821-1-088	NO
10-821-1-095	NO

10-821-2-XX

PART NUMBER	RoHS COMPLIANT
10-821-2-01	YES
10-821-2-03	YES
10-821-2-035	YES
10-821-2-04	YES
10-821-2-044	YES
10-821-2-05	NO
10-821-2-088	NO
10-821-2-095	NO

10-821-3-XX

PART NUMBER	RoHS COMPLIANT
10-821-3-01	YES
10-821-3-03	YES
10-821-3-035	YES
10-821-3-04	YES
10-821-3-044	YES
10-821-3-05	NO
10-821-3-088	NO
10-821-3-095	NO

Continued on next page...

RoHS COMPLIANCE CONTINUED:

10-821-4-XX

PART NUMBER	RoHS COMPLIANT
10-821-4-01	YES
10-821-4-03	YES
10-821-4-035	YES
10-821-4-04	YES
10-821-4-044	YES
10-821-4-05	NO
10-821-4-088	NO
10-821-4-095	NO

TOOLING:

INSTALLATION TOOL: ARBOR PRESS	INSTALLATION TOOL: ANVIL (ARBOR PRESS OPERATED)	INSTALLATION TOOL: PRESS-FIT / ROLL SWAGE / RIVET PUNCH (ARBOR PRESS OPERATED)	INSTALLATION TOOL: FLARE SWAGE PUNCH (ARBOR PRESS OPERATED)
TM1	TA125-40-21	TP93-T40	N/A

NOTES:

DATASHEET NOTES
N/A

INSTRUCTION NOTES
SEE GENERAL SWAGING INSTALLATION INSTRUCTION ON CONCORD ELECTRONICS' WEBSITE <a href="http://WWW.CONCORD-ELECTRONICS.COM">WWW.CONCORD-ELECTRONICS.COM</a> .