

CABLE ASSEMBLIES

BNC MALE / MALE



SHIELD MIC.	RG58C/U	RG59B/U	RG62A/U	LENGTH
795-5220	795-2560	795-5200	795-5210	18 inches
795-5221	795-2561	795-5201	795-5211	24 inches
795-5222	795-2562	795-5202	795-5212	30 inches
795-5223	795-2563	795-5203	795-5213	36 inches
795-5224	795-2564	795-5204	795-5214	48 inches
795-5225	795-2565	795-5205	795-5215	60 inches

1ST END- BNC male
Plated brass body
Gold plated brass
center contact.

CABLE
Shielded Mic.50
RG58C/U (50 OHM)
RG59B/U (75 OHM)
RG62A/U (93 OHM)

2ND END-
Same as 1st end.

TNC MALE / TNC MALE



RG58C/U	LENGTH
795-5299	12 inches
795-5285	18 inches
795-5286	24 inches
795-5287	36 inches
795-5288	48 inches
795-5289	60 inches

1ST END- TNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.

CABLE- RG58C/U

2ND END- Same as 1st end.

BNC MALE / FEMALE



RG58C/U	LENGTH	1ST END-
795-3031	12 inches	BNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.
795-3032	24 inches	
795-3033	36 inches	CABLE- RG58C/U
795-3034	48 inches	
795-3035	60 inches	2ND END- BNC female. Plated brass body. Gold plated beryllium copper contact. 50 OHM impedance.

BNC MALE ONE END ONLY



RG58C/U	RG59B/U	LENGTH	1ST END-
795-5230	795-5235	12 inches	BNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.
795-5231	795-5236	24 inches	
795-5232	795-5237	36 inches	
795-5233	795-5238	48 inches	CABLE- RG58C/U or RG59B/U
795-5234	795-5239	60 inches	

BNC FEMALE / FEMALE



RG58C/U	LENGTH	1ST END-
795-3021	12 inches	BNC female. Plated brass body. Gold plated beryllium copper center contact. 50 OHM impedance.
795-3022	24 inches	
795-3023	36 inches	CABLE- RG58C/U
795-3024	48 inches	
795-3025	60 inches	2ND END- Same as 1st end.

SMA MALE / BNC MALE



RG316/U	LENGTH	1ST END-
795-5295	24 inches	Crimp SMA male. Passivated steel shell. Gold plated center contact.
795-5296	48 inches	
795-5297	60 inches	CABLE- RG316/U
		2ND END- BNC male. Plated brass body. Gold plated brass center contact.

BNC MALE / TNC MALE



RG58C/U	LENGTH	1ST END-
795-5245	12 inches	BNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.
795-5246	24 inches	
795-5247	36 inches	CABLE- RG58C/U
795-5248	48 inches	
795-5249	60 inches	2ND END- TNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.

BNC MALE TO RIGHT ANGLE BNC MALE



RG58C/U	LENGTH	1ST END-
795-5240	18 inches	BNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.
795-5241	24 inches	
795-5242	36 inches	CABLE- RG58C/U
795-5243	48 inches	
795-5244	60 inches	2ND END- Right angle BNC male. Plated brass body. Gold plated brass center contact. 50 OHM impedance.

