MICRO SWITCH
FREEPORT ILLINOIS, U S A
A DIVISION OF HONEYWELL
FED. MFG. CODE 01929

SWITCH-TOGGLE (MAGNETIC HOLD-IN)

CATALOG LISTING
25ET79-S



CIRCUIT DIAGRAM (MECHANICALLY MAINTAINED POSITION)



NOTES
1 - EXPOSED PARTS ARE OF CORROSION RESISTANT MATERIAL OR ARE SUITABLY PROTECTED TO PREVENT CORROSION. ENCLOSURE FINISHED WITH BLUE EPOXY BASED ENAMEL COLOR NO. 25184 PER FEDERAL STANDARD 595
2 - SWITCH SEALED PER MIL-S-5594
3 HOLD IN VOLTAGE: THE MINIMUM SPECIFIED VOLTAGE AT WHICH THE LEVER WILL REMAIN ACTUATED. HOLD IN MAY OCCUR AT A LOWER VALUE.
DROP OUT VOLTAGE: THE VOLTAGE RANGE IN WHICH THE LEVER WILL BE RELEASED
4 - CIRCUITS CAN BE TRANSFERRED MANUALLY. ENERGIZING THE COIL WILL NOT CAUSE TRANSFER OF CIRCUITS
5 CIRCUIT IDENTIFICATION IS SHOWN ON SWITCH
6 NAS 600-3P SCREW (5) OR EQUIVALENT
NAS 620-C4 FLAT WASHER (5)
MS35338-135 LOCKWASHER (5)
7 - THE DIODES ARE JANTX TYPE AND LIMIT THE EMI: SPIKES (TRANSIENTS OF DURATION LESS THAN 500 MICRO SECONDS) GENERATED BY THE SWITCH COIL SHALL NOT EXCEED +42 VOLTS OR -14 VOLTS ABSOULTE
8 HARDWARE MAY BE FURNISHED UNASSEMBLED PER MIL-S-5594
9 FORCE TO BE APPLIED AT THIS POINT IN A DIRECTION PERPENDICULAR TO THE LEVER LONGITUDINAL AXIS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

SCALE FULL
DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/m	DIM. in	TOL. mm/in
NO PLACES	X	1/.04		
ONE PLACE	X.X	0.4/.016	X.X	0.8/.03
TWO PLACES	X.XX	0.15/.008	X.XX	0.3s/.015
THREE PLACES			X.XXX	0.13/.005
ANGLES				

DESIGN UNITS ☐ METRIC ■ US CUSTOMARY

RAW MATERIAL-COMMERCIAL STANDARD
MICRO SWITCH STANDARDS APPLY
DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED

WEIGHT 4.0 OZ MAX

CHARACTERISTICS 3

SOLENOID RATING AT 20°C

STEADY STATE LIMITS	20-30 VDC
HOLD-IN	10 VDC
DROP OUT	1.5-10 VDC
COIL RESISTANCE	220 OHM MIN
OVERRIDE FORCE AT 30 VDC 9	2.5-10 LB
OPERATING FORCE AT 30 VDC 9	1-7 LB

ELECTRICAL DATA

CONTACT ARRANGEMENT
SPDT

VOLTAGE	RATING IN AMPERES							
	SEA LEVEL			65,000 FT				
	RES	IND	MOTOR		RES	IND	MOTOR
28 VOLTS DC	4	3	4		4	2.5	4

REVISIONS

A	PR6687	S L B 31 AUG 77	
B	CO 39462	S L B 21 DEC 77	
C	CO 44768	G A S 19 AUG 78	
D	CO 45291	T M M 11 DEC 78	
E	C047008	J A P 7 DEC 79	
F	C049806	D J W 25 SEPT 81	
G	CO 53402	MAM 16 APR 84	
H	C059021A	JAS 27 FEB 86	
J	CO 75787-E	DLT 7 JUL 94	
K	C093048	GJW 12 NOV 98	
L	0012413	VK 22 APR 05	

25ET79-S PAGE 1 OF 1
RELEASE NO. PR-6687 REPLACES
DRAWING NUMBER M
ISSUE 12
CHECK 22 APR 05
AK CHECK 29 JUN 77
DRAWN SL BLUM 28 JUNE 77
FORMTEK FO-62851-A