




Home > Products > MICRO SWITCH™ Sealed and High Accuracy Switches > AT > Product Page

### Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

## 64AT34-3D



Actual product appearance may vary.

**AT Series Toggle Switch, 4 pole, 2 position, H58 terminal, Locking Lever**

### Features

Gold or silver contacts  
 Choice of sealed bushing  
 Standard or pull to unlock toggle lever  
 Short behind-panel depth  
 Solder or quick connect termination  
 2,4, 6, or 8 SPDT precision basic switches  
 2 or 3 position, momentary or maintained action

### Potential Applications

Industrial machinery and equipment  
 Military and commercial aviation  
 Construction equipment  
 Test instruments  
 Agricultural machinery  
 Process control  
 Medical instrumentation

### Description

Compact multipole 2, 4, 6, or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull-to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MIL-8805/98. Various levers and styles are available.

### Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

### My Links

[Login to iCOM](#)  
[Login as Rep/AD](#)  
[Login as Guest](#)  
[Login to Digital University](#)

### Keyword Search

Search for product and support information.

All Sensing and Control

### Product Search

Part number search:

Use (\*) to expand search

[Specification Search](#)

Product Specifications																																		
Circuitry/Operating action	<table border="0"> <tr> <td></td> <td style="text-align: center;"><b>Keyway</b></td> <td style="text-align: center;"><b>Opposite Keyway</b></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Maintained</b></td> <td style="text-align: center;"><b>Maintained</b></td> </tr> <tr> <td></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td></td> <td style="text-align: center;">NC COM NO</td> <td style="text-align: center;">NC COM NO</td> </tr> <tr> <td></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td></td> <td style="text-align: center;">NC COM NO</td> <td style="text-align: center;">NC COM NO</td> </tr> <tr> <td></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td></td> <td style="text-align: center;">NC COM NO</td> <td style="text-align: center;">NC COM NO</td> </tr> <tr> <td></td> <td style="text-align: center;"></td> <td style="text-align: center;"></td> </tr> <tr> <td></td> <td style="text-align: center;">NC COM NO</td> <td style="text-align: center;">NC COM NO</td> </tr> <tr> <td></td> <td style="text-align: center;"><b>ON</b></td> <td style="text-align: center;"><b>OFF</b></td> </tr> </table>		<b>Keyway</b>	<b>Opposite Keyway</b>		<b>Maintained</b>	<b>Maintained</b>					NC COM NO	NC COM NO					NC COM NO	NC COM NO					NC COM NO	NC COM NO					NC COM NO	NC COM NO		<b>ON</b>	<b>OFF</b>
	<b>Keyway</b>	<b>Opposite Keyway</b>																																
	<b>Maintained</b>	<b>Maintained</b>																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	<b>ON</b>	<b>OFF</b>																																
Product Type	MICRO SWITCH™ Toggle																																	
Ampere/Voltage Range (Resistive Load)	0.1 A to 1.0 A at 0.5 Vac to 115 Vac, 0.1 A to 1.0 A at 0.5 Vdc to 28 Vdc																																	
Circuitry	4PDT																																	
Action	2 position																																	
Mounting	Bushing 15/32 in																																	
Termination	H58																																	
Comment	FAA-PMA approved, contains 24K solid gold contacts																																	
Availability	Global																																	
UNSPSC Code	30211908																																	
UNSPSC Commodity	30211908 Toggle switches																																	
Series Name	AT																																	