

## Honeywell Sensing and Control

Search



### SSCDANN015PG2A3

( Home : [Products](#) : [Sensors](#) » [Silicon Pressure Sensors](#) » [Low Pressure Sensors](#) » [TruStability® SSC](#) )

#### narrow your search

##### Products

- [Controls Monitoring and Lighting](#) (286)
- [Machine Safety](#) (1727)
- [Sensors](#) (6158)
- [Switches](#) (9781)
- [Wireless](#) (45)

##### Technology

- [Control and Instrumentation](#) (890)
- [Electromechanical](#) (9303)
- [Magnetic](#) (538)
- [Platinum thin film](#) (56)
- [Thick Film](#) (1372)
- [More...](#)



Actual product appearance may vary.

TruStability® SSC Series-Standard Accuracy, ±2% total error band, digital I<sup>2</sup>C address: 0x28, DIP, AN: single axial barbed port, gage, 0 psi to 15 psi, 3.3 Vdc, dry gases only, no special options

[Sales & Service](#)

[Distributor Inventory](#)

[Overview](#)  
 [Specs](#)  
 [Documentation](#)  
 [Application Notes](#)

#### Product Specifications

Measurement Type	Gage
Signal Conditioning	Amplified
Pressure Range	0 psi to 15 psi
Overpressure	30 psi
Supply Voltage	3.3 Vdc
Supply Current	1.6 mA typ.
Temperature Compensation	Yes
Output Calibration	Yes
Response Time	1 ms max.
Port Style	AN: single axial barbed port
Package Type	DIP
Accuracy (Best Fit Straight Line)	±0.25%
Shock	MIL-STD-202F, Method 213B, Condition F
Vibration	MIL-STD-202F, Curve AK (20.7 g random)
Operating Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Compensated Temperature Range	-20 °C to 85 °C [-4 °F to 185 °F]
Storage Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Media Compatibility	Dry gases only
Comment	No special options
Availability	Global
Series Name	TruStability® SSC

#### contacts

[Customer Service](#)  
[Technical Support](#)  
[Global Sales & Service](#)  
[View Site Demo](#)  
[Site Comments?](#)

#### meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



Meet Dr. Larry

#### my links

[Login to iCOM](#)  
[Login to Rep/AD Portal](#)  
[Login to Digital University](#)

#### News Center

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

#### MICRO SWITCH Anniversary site

#### new products

##### New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



[Wireless Web Site WGLA and WPMM XYR6000™](#)

[find out more](#)

#### white papers

- [Wireless Switches Offer Unlimited Benefit](#)
- [Basic Switches Are Not Created Equal](#)
- [Applying Precision Switches](#)
- [Sensors for Medical Devices](#)
- [New Ways to Measure Torque](#)
- [Choosing Safety Switches](#)
- [Specifying Hour Meters](#)

#### Need help?

[Click here to contact us](#)