

REDINGTON COUNTERS, INC.
P.O. Box 608, 130 Addison Road, Windsor, CT 06095
Toll Free: (860) 688-6205 • Fax: 860/688-1591
E-Mail: Info@RedingtonCounters.com • Website: www.RedingtonCounters.com

Item # 3301-0000, Non-Reset Model



Non-Reset Model

The Redington Model 33 line of LCD counters provides a large display, 7mm high figures, in an eight digit counter. The counters are available in a variety of mountings: 2-hole rectangular, 3-hole round, flush-round and flush-rectangular. Voltage operating ranges are 10-277 VDC and 20-277VAC. All models are totally sealed from moisture and dirt and conform to NEMA 4 and 4X specifications when mounted with the optional gasket. Their rugged construction makes them ideal replacements for current electromechanical counters. Units have polarized LCD for high visibility in sunlight.

SPECIFICATIONS

Model No.	33
Mounting	2-Hole Rectangular
Display	LCD with large 0.28 inch (7mm) high Figures, black on light background
Display Height	0.28 Inch
Display Height	7 mm
No. of Digits	8
Max. Count/Displays	99999999
Voltage	10-277 VDC 20-277 VAC
Vih	10VDC min. 20VAC
Vil	3VAC 3VDC max.
Battery Life	7+ year
Speed	25 counts per second
Shock	44 to 55g's, SAE J1378
Vibration	20 g
Humidity	95% SAE J1378
Operating Temperature	-40 to +185 °F
Operating Temperature	-40 to +85 °C
Sealing	Totally sealed, panel gaskets-NEMA 4 and 4X
Approvals	CE compliant UL/cUL recognized (file no. ELIY2.E36690)
Termination	0.250 inch (6.4mm) spades

Case Material	Polymer (black)
Panel Cutout	1.45 x 0.95 (Front) Inch 1.42 x 0.90 (Behind) Inch
Panel Cutout	22.9 x 36.1 (Behind) mm 24.0 x 37.0 (Front) mm
Weight	1 oz
Weight	28 gm
Stock Availability	Yes