



## Flexible Conduits & Fittings

### T&B Catalog Number:

CYLG-36S.30

### UPC Number:

78620995464

### Status:

Active

### Description:

Coarse profile medium wall very flexible gray conduit. (CYL) Material - polyamide 6, conduit size NW - 36.

### Application

Machine

Installation Industries

### Characteristics

Very good flexibility

Good impact strength, also at low temperatures and dry conditions

Self-extinguishing, free from halogens and cadmium

### General

Material	Polyamide 6
Material-Conduit Core	Non-Metallic
Color	Gray
System	PMAFLEX
Compatible With	PMAFIX Pro, PMAFIX, PMA Smart Line, PMAGRIP

### Dimension Information

Conduit Size (inches)	1 1/4
Conduit Size NW (mm)	36
Conduit Size Metric (mm)	40
Outside Diameter (inches)	1.67
Inside Diameter (mm)	36
Outside Diameter (mm)	42.5
Static Radius (mm)	60
Rec. Fitting Thread-Metric	M40 x 1.5
Rec. Fitting Thread-PG	36

### Technical Information

Temperature Range-Continuous (Celsius)	-40 to +105
Temperature-Short-Term (Celsius)	160
Fatigue Life	High
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

### Packaging

T&B Order Multiple	1
T&B Inner Pack	1
Package in Units	6
T&B Sold in UOM	Each
T&B Weight Per UOM	0.11 lbs. Each

### Application Support

PMA Reference Guide	Available on Website
PMA Conduit Guide	Available on Website
Product Overview-PMAFLEX Conduits	Available on Website

### Certifications

RoHS Compliance

Yes

## Certifications



### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)