

Product Details for 2112D9NE



2112D9NE

Tyco Part Number:
1423152-2

[Active](#)

Time Delay Relays

[Not ELV or RoHS Compliant](#)

Product Highlights:

- ? 2100 Miniature Timing Series
- ? Time Delay Relay
- ? Input Voltage = 28 VDC
- ? Contact Arrangement = 2 Form C, DPDT, 2 C/O
- ? Contact Rating = 10A @ 120 VAC

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us](#)
- [About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? None Available

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Time Delay Relay
- ? Termination Type = Solder Hook Terminals

Electrical Characteristics:

- ? Input Voltage (VDC) = 28
- ? Contact Rating = 10A @ 120 VAC

Body Related Features:

- ? [Series](#) = 2100 Miniature Timing

Contact Related Features:

- ? Mounting Options = Mounting Holes
- ? Mode of Operation = On-Delay
- ? Delay Time = 0.750 seconds to 10 seconds
- ? Type of Control = Internal Key
- ? Repeatability, Max. = $\pm 5\%$ @ 25 °C, $\pm 7\%$ @ 85 °C, $\pm 8\%$ @ 55 °C
- ? Approved Standards = CE Approved
- ? Approx. Dimensions (L x W x H) (mm [in]) = 63.50 x 38.60 x 123.90 [2.501 x 1.520 x 4.881]

Configuration Related Features:

- ? [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- ? Multiple Timing Ranges = Without

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not suitable for lead free processing

Conditions for Usage:

- ? Temperature Range (°C) = -55 – +85

Other:

- ? Brand = Agastat