

## Product Details for SCBRX012XXAAXA



### SCBRX012XXAAXA

Tyco Part Number: 1-1437467-1

[Active](#)

### Time Delay Relays

[Not ELV or RoHS Compliant](#)

#### Product Highlights:

- ? SCB Specification Grade Precision Timing Series
- ? Time Delay Relay
- ? Input Voltage = 120 VAC
- ? Input Voltage = 125 VDC
- ? Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us](#)
- [About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

? None Available

#### Catalog Pages/Data Sheets:

? None Available

#### Product Specifications:

? None Available

#### Application Specifications:

? None Available

#### Instruction Sheets:

? None Available

#### CAD Files:

? None Available

#### Additional Information:

? [Product Line Information](#)

#### Related Products:

? [Tooling](#)

### Product Features

(Please use the Product Drawing for all design activity)

#### Product Type Features:

- ? Product Type = Time Delay Relay
- ? Termination Type = 8-Pin Octal Style Plug
- ? Comment = Does not include socket.

#### Electrical Characteristics:

- ? Input Voltage (VAC) = 120
- ? Input Voltage (VDC) = 125
- ? Contact Rating = 10A Resistive @ 28 VDC/120 VAC

#### Body Related Features:

- ? [Series](#) = SCB Specification Grade Precision Timing

#### Contact Related Features:

- ? Mounting Options = Socket
- ? Mode of Operation = On-Delay
- ? Delay Time = 0.1 seconds to 3 seconds
- ? Type of Control = Knob
- ? Repeatability, Max. = ± 0.5% +4 msec
- ? Approved Standards = CE Approved, CSA Certified, FM Approved, UL Recognized
- ? Approx. Dimensions (L x W x H) (mm [in]) = 50.00 x 50.00 x 83.00 [1.970 x 1.970 x 3.270]

#### Configuration Related Features:

- ? [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- ? Multiple Timing Ranges = Without

#### Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- ? Temperature Range ( °C) = -30 – +65

#### Other:

- ? Brand = Agastat