

## SCBRX012XXACXA Product Details



### SCBRX012XXACXA

(1-1437467-5)

TE Part Number: 1-1437467-5

 [Active](#)

 [Add to Part List](#)

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- SCB Specification Grade Precision Timing Series
- Time Delay Relay
- Input Voltage = 120 VAC
- Input Voltage = 125 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#) | 
 [Find Similar Products](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

**NEW!**

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 8-Pin Octal Style Plug
- Comment = Does not include socket.

#### Electrical Characteristics:

- Input Voltage (VAC) = 120
- Input Voltage (VDC) = 125
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC

#### Body Related Features:

- [Series](#) = SCB Specification Grade Precision Timing

#### Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = On-Delay
- Delay Time = 1 second to 30 seconds
- Type of Control = Knob
- Repeatability, Max. = ±0.5% +4 msec
- Approved Standards = CE Approved, CSA Certified, FM Approved, UL Recognized
- Approx. Dimensions (L x W x H) (mm [in]) = 50.00 x 50.00 x 83.00 [1.970 x 1.970 x 3.270]

#### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- Temperature Range (°C) = -30 - +65

#### Other:

- Brand = Agastat