


## SRC72ANNA Product Details



### SRC72ANNA (8-1437479-4)

TE Part Number: 8-1437479-4

 [Active](#)

 [Add to Part List](#)

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- SRC Specification Grade Repeat Cycle Timing Series
- Time Delay Relay
- Input Voltage = 120 VAC
- Input Voltage = 120 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#) | 
 [Find Similar Products](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

**NEW!**

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Dimensional Drawing](#)
- [Wiring Diagram](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 8-Pin Octal Style Plug

#### Electrical Characteristics:

- Input Voltage (VAC) = 120
- Input Voltage (VDC) = 120
- Contact Rating = 10A Resistive @ 28 VDC/120 VAC

#### Body Related Features:

- [Series](#) = SRC Specification Grade Repeat Cycle Timing

#### Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = Repeat Cycle
- Type of Control = Knob
- Repeatability, Max. =  $\pm 1\%$  +4 msec
- Approved Standards = CE Approved
- Approx. Dimensions (L x W x H) (mm [in]) = 50.00 x 50.00 x 94.00 [1.970 x 1.970 x 3.703]

#### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = With
- Timing Range Off-Time = 1 minute to 30 minutes
- Timing Range On-Time = 1 minute to 30 minutes

#### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- Temperature Range (°C) = -30 - +65

#### Other:

- Brand = Agastat