

## STARX012XSARXA Product Details



### STARX012XSARXA

TE Part Number: 2-1437476-4

 [Active](#)

 [Add to Part List](#)

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- STA Specification Grade Tab-Type Precision Timing Series
- Time Delay Relay
- Input Voltage = 120 VAC
- Input Voltage = 125 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#) | 
 [Find Similar Products](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

## Documentation & Additional Information

### Product Drawings:

- None Available

### Catalog Pages/Data Sheets:

- None Available

### Product Specifications:

- None Available

### Application Specifications:

- None Available

### Instruction Sheets:

- None Available

### CAD Files:

- None Available

### Additional Information:

- [Product Line Information](#)

### Related Products:

- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

### Product Type Features:

- Product Type = Time Delay Relay
- Termination Type = 11 Pin Tab-Type Plug-In Terminals

### Electrical Characteristics:

- Input Voltage (VAC) = 120
- Input Voltage (VDC) = 125
- Contact Rating = 10A @ 28 VDC

### Body Related Features:

- [Series](#) = STA Specification Grade Tab-Type Precision Timing

### Contact Related Features:

- Mounting Options = Socket
- Mode of Operation = On-Delay
- Delay Time = 2 hours to 48 hours
- Type of Control = Knob
- Repeatability, Max. =  $\pm 0.5\%$  +4 msec
- Approved Standards = CE Approved, CSA Certified, FM Approved, UL Recognized
- Approx. Dimensions (L x W x H) (mm [in]) = 38.00 x 35.00 x 77.00 [1.497 x 1.379 x 3.033]

### Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- Multiple Timing Ranges = Without
- Status Indication = Control and Output Indicator Lamps

### Industry Standards:

- [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- [Lead Free Solder Processes](#) = Not suitable for lead free processing

### Conditions for Usage:

- Temperature Range (°C) = -30 - +65

### Other:

- Brand = Agastat