

## STARX022XSABXA Product Details



### STARX022XSABXA

(7 - 1437476 - 7)

TE Internal Number: 7 - 1437476 - 7

 [Active](#)
 [Add to Part List](#)

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- ? STA Specification Grade Tab -Type Precision Timing Series
- ? Time Delay Relay
- ? Input Voltage = 120 VAC
- ? Input Voltage = 125 VDC
- ? Contact Arrangement = 2 Form C, DPDT, 2 C/O

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)



### Documentation & Additional Information

#### Product Drawings:

- ? None Available

#### Catalog Pages/Data Sheets:

- ? None Available

#### Product Specifications:

- ? None Available

#### Application Specifications:

- ? None Available

#### Instruction Sheets:

- ? None Available

#### CAD Files:

- ? None Available

#### Additional Information:

- ? [Product Line Information](#)

#### Related Products:

- ? [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- ? Product Type = Time Delay Relay
- ? Termination Type = 11 Pin Tab -Type Plug -In Terminals

#### Electrical Characteristics:

- ? Input Voltage (VAC) = 120
- ? Input Voltage (VDC) = 125
- ? Contact Rating = 10A @ 28 VDC

#### Body Related Features:

- ? [Series](#) = STA Specification Grade Tab -Type Precision Timing

#### Contact Related Features:

- ? Mounting Options = Socket
- ? Mode of Operation = Off -Delay
- ? Delay Time = 0.5 seconds to 15 seconds
- ? Type of Control = Knob
- ? Repeatability, Max. = ± 0.5% +4 msec
- ? Approved Standards = CE Approved, CSA Certified, FM Approved, UL Recognized
- ? Approx. Dimensions (L x W x H) (mm [in]) = 38.00 x 35.00 x 77.00 [1.497 x 1.379 x 3.033]

#### Configuration Related Features:

- ? [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- ? Multiple Timing Ranges = Without
- ? Status Indication = Control and Output Indicator Lamps

#### Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not suitable for lead free processing

#### Conditions for Usage:

- ? Temperature Range (°C) = -30 – +65

#### Other:

- ? Brand = Agastat