

VTM2ECD Product Details



VTM2ECD

(7 - 1437481 - 8)

TE Internal Number: 7 - 1437481 - 8

 [Active](#)
 [Add to Part List](#)

Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ? VTM2 Off -Delay Timing Module Series
- ? Time Delay Relay
- ? Input Voltage = 24 VAC
- ? Input Voltage = 24 VDC
- ? Contact Arrangement = 1 Form A, SPST-NO, 1 N/O Solid State

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)
- [Request Samples](#)



Documentation & Additional Information

Product Drawings:

- ? None Available

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Additional Product Images:

- ? [Dimensional Drawing](#)
- ? [Wiring Diagram](#)

Related Products:

- ? [Tooling](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Time Delay Relay
- ? Termination Type = .250 x .032 Quick Connect Terminals

Electrical Characteristics:

- ? Input Voltage (VAC) = 24
- ? Input Voltage (VDC) = 24
- ? Contact Rating = 1A

Body Related Features:

- ? [Series](#) = VTM2 Off -Delay Timing Module

Contact Related Features:

- ? Mounting Options = Mounting Holes
- ? Mode of Operation = Off -Delay
- ? Delay Time = 0.5 seconds to 10 seconds
- ? Type of Control = External Resister
- ? Repeatability, Max. = +1%
- ? Approved Standards = CSA Certified, UL Recognized
- ? Approx. Dimensions (L x W x H) (mm [in]) = 50.80 x 50.80 x 22.48 [2.001 x 2.001 x .885]

Configuration Related Features:

- ? [Contact Arrangement](#) = 1 Form A, SPST -NO, 1 N/O Solid State
- ? Multiple Timing Ranges = Without

Industry Standards:

- ? [RoHS/ELV Compliance](#) = Not ELV/RoHS compliant
- ? [Lead Free Solder Processes](#) = Not suitable for lead free processing

Conditions for Usage:

- ? Temperature Range (°C) = -40 - +65

Other:

- ? Brand = Agastat