

## SST120AA Product Details



### SST120AA

(1-1437481-2)

TE Internal Number: 1-1437481-2

Active

### Time Delay Relays

[Not EU RoHS or ELV Compliant](#)

#### Product Highlights:

- SST Industrial Grade Timing Series
- Input Voltage = 24 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Rating = 10A Resistive @ 120/240 VAC
- Mounting Options = Socket

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>• None Available</li> </ul>	<p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Product Line Information</a></li> </ul> <p><b>Additional Product Images:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Dimensional Drawing</a></li> <li>• <a href="#">Wiring Diagram</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Tooling</a></li> </ul>

Product Features (Please use the Product Drawing for all design activity)	
<p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>• Termination Type = 8-Pin Octal Style Plug</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>• Input Voltage (VDC) = 24</li> <li>• Contact Rating = 10A Resistive @ 120/240 VAC</li> </ul> <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Series</a> = SST Industrial Grade Timing</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>• Mounting Options = Socket</li> <li>• Mode of Operation = On-Delay</li> <li>• Delay Time = 0.1 seconds to 10 seconds</li> <li>• Type of Control = Knob</li> <li>• Repeatability, Max. = ± 1%</li> <li>• Approved Standards = CSA Certified, UL Recognized</li> <li>• Approx. Dimensions (L x W x H) (mm [in]) = 50.80 x 50.80 x 101.90 [2.001 x 2.001 x 4.014]</li> </ul>	<p><b>Configuration Related Features:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">Contact Arrangement</a> = 2 Form C, DPDT, 2 C/O</li> <li>• Multiple Timing Ranges = Without</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>• <a href="#">RoHS/ELV Compliance</a> = Not ELV/RoHS compliant</li> <li>• <a href="#">Lead Free Solder Processes</a> = Not suitable for lead free processing</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>• Temperature Range (?C) = -23 - +54</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>• Brand = Agastat</li> </ul>

### Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

### Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)