

[My Cart](#) | [My Part Lists](#) | [Sign In](#) | [Register](#)English [\(Change\)](#)

Search by Keyword or Part #

## 3-1825139-9 Product Details

[Live Product Chat](#)**3-1825139-9**

TE Internal Number: 3-1825139-9

[Active](#)

### Toggle Switches

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

#### Product Highlights:

- A Series
- Double Pole - Three Throw Configuration (Pole-Throw)
- Current Rating = 5 A
- Mount Style = Panel
- Termination Type = Vertical, Wire Lugs

[View all Features](#)

### Quick Links

[Check Pricing & Availability](#)  
[Search for Tooling](#)  
[Product Feature Selector](#)  
[Contact Us About This Product](#)

[Add to My Part List](#)[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [GEMINI A SERIES TOGGLE SWITCH, DOUBLE POLE, 3 POSITI...](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Configuration (Pole-Throw) = Double Pole - Three Throw
- Termination Type = Vertical, Wire Lugs
- Comment = UL available when ordering - consult factory.

#### Electrical Characteristics:

#### Housing Related Features:

- Toggle Style = Baton Standard
- Toggle Length (mm [in]) = 10.40 [0.410]
- Process Sealed = No
- Bushing Style = Threaded
- Bushing Type = 1/4-40

- Current Rating (A) = 5

**Termination Related Features:**

- Seal Type = Terminal Seal (Insert Molded)

**Body Related Features:**

- Series = A
- Mount Style = Panel
- Flammability Rating = UL 94V-0

**Contact Related Features:**

- Contact Plating = Silver

**Configuration Related Features:**

- [Operating Function](#) = On On On

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

**Other:**

- Brand = Alcoswitch

**Corporate Information**

[Who We Are](#)  
[Investors](#)  
[News Room](#)  
[Supplier Portal](#)  
[Careers](#)

**Quick Links**

[Check Distributor Inventory](#)  
[Cross Reference](#)  
[Find Documents & Drawings](#)  
[Product Compliance Support Center](#)  
[Site Map](#)

**Customer Support**

[Email or Chat with Us](#)  
[Find a Phone Number](#)  
[Search Knowledge Base](#)  
[Manage Your Account](#)