


[My Cart](#)

[My Part Lists](#) | [Sign In/Register](#)
[English \(Change\)](#)
**Have a Question?**


Chat with a Product Information Specialist

What can we help you find?


[Products](#) | [Industries](#) | [Resources](#) | [About TE](#) | [Support Center](#) | [My Account](#)
**1825165-1 Product Details**

[Share](#)

[Print](#)

[Email](#)

**1825165-1**

TE Internal Number: 1825165-1


[Active](#)
**Slide Switches**

[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)
**Product Highlights:**

- 4 Positions
- Double Pole - Four Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Black
- STS Series

[View all Features](#)
**Quick Links**

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)
**Documentation & Additional Information**
**Product Drawings:**

- [SLIDE SWITCH \(DP4T\) STS2400PC SERIES](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)
**Product Features (Please use the Product Drawing for all design activity)**
**Product Type Features:**

- Configuration (Pole-Throw) = Double Pole - Four Throw
- Actuator Style = Top
- Series = STS
- Mount Angle = Vertical
- Terminal Configuration = Standard
- Grade = Economy
- Termination Type = PC

**Electrical Characteristics:**

- Contact Rating = 300mA @ 125 VAC

**Body Features:**

- [Number of Positions](#) = 4
- Actuator Color = Black
- Mount Style = Through-Hole
- Switch Style = Low Profile
- PCB Tail Length (mm [in]) = 2.79 [0.110]
- Actuator Material = Polyester
- Actuator Travel = 2.50 [.098]

**Contact Features:**

- Contact Plating = Silver

**Housing Features:**

- UL Flammability Rating = UL 94-HB

**Configuration Features:**

- Number of Actuators = Single

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

**Identification Marking:**

- Stamped Marking = With

**Other:**

- Brand = Alcoswitch

**Corporate Information**
[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
**Quick Links**
[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)
**Customer Support**
[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage your Account](#)
**Keep Me Informed**

Receive TE News, Events &amp; Technology Updates

Enter your email address

**Follow Us On:**
