



Search by Keyword or Part #

TTE13D2T Product Details

Have a Question?

Chat with a Product Information Specialist



TTE13D2T
(9-1437562-4)
TE Internal Number: 9-1437562-4
 [Active](#)

Toggle Switches

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- TT (Tiny) Series
- Single Pole - Double Throw Configuration (Pole-Throw)
- Current Rating = 3 A
- Mount Style = Panel
- Termination Type = Wire Lugs

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • ALCOSWITCH PRODUCTS (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Dimensional Drawing <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Configuration (Pole-Throw) = Single Pole - Double Throw • Termination Type = Wire Lugs <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Current Rating (A) = 3 <p>Termination Related Features:</p> <ul style="list-style-type: none"> • Seal Type = Terminal Seal (epoxy), Environmental <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = TT (Tiny) • Mount Style = Panel <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Contact Plating = Silver 	<p>Housing Related Features:</p> <ul style="list-style-type: none"> • Toggle Style = Baton Medium • Toggle Length (mm [in]) = 7.52 [0.296] • Process Sealed = No • Bushing Style = Splashproof, Threaded • Bushing Type = 10-48 <p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Operating Function = On None On <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C <p>Other:</p> <ul style="list-style-type: none"> • Brand = Alcoswitch • Comment = Each switch is provided with a disposable boot used only during cleaning operation.



Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)

Sign up for our eNewsletter

Enter your email address

Follow Us On:

[Twitter](#) [Facet](#) [Flickr](#) [Linke](#) [YouTu](#)

Visit Us On:



[Provide Website Feedback](#)