EM5035 Series EuroMag Terminal Blocks

Pluggable Block, Stackable (Mates with EM5045 Series) 5.00 Centers

SPECIFICATIONS

Rating: 10A, 300V Center Spacing: 0.197" (5.00mm) Wire Range: #16-24 AWG Housing Material: Black UL 94V0 Thermoplastic Contact Material: Tin-Plated Brass Wire Protector: Phosphor Bronze, Tin-Plated Screw Size: M2.6 Chromatized Steel Operating Temperature: 105°C (221°F) max., -40°C (-40°F) min. Torque Rating: 3.0 lb-in. Construction: Modular design features dovetails for

Agency Information: Nu File E62622; CE Certified

Poles	L (mm)	Poles	L (mm)
2 3 4 5 6 7 8 9 10 11 12 13	10.0 15.0 20.0 25.0 30.0 35.0 40.0 45.0 50.0 55.0 60.0 65.0	14 15 16 17 18 19 20 21 22 23 24	70.0 75.0 80.0 90.0 95.0 100.0 105.0 110.0 115.0 120.0

To convert to inches, divide by 25.4

Part Numbering System

Series

of Poles


EM5035


02 to **24**



Shown with EM5045series header - order seperately

Dimensions - mm (in)





Mating Header: EM5045 pg. 106