



Datasheet for part number DBMG-25S-J-A197

|   |
|---|
| Our Catalog Part Number: DBMG-25S-J-A197                              |
| Our Global Manufacturing Part Number: 053513-2748                     |
| Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M |

| Product Datasheet               |  |
|---------------------------------|--|
| General                         | D*M High reliable D-Sub Connectors   |
| Wire Gauge Range AWG            | AWG 20-28  |
| Mating Cycles                   | 200  |
| Contact Arrangement             | 25 contacts size 20  |
| Dielectric Withstanding Voltage | 1000 VAC at sea level  |
| Current Rating                  | 7.5 A max  |
| Contact Resistance              | 7.5 milli Ohm max  |
| Operating Temperature           | -55°/+125°   |
| Salt Spray Test                 | 20 hours   |
| Shell Material                  | Steel  |
| Shell Finish                    | Pure tin over nickel   |
| Insulator Material              | Thermoplastic, type PCT UL 94V-0   |
| Insulator Color                 | black  |
| Gender                          | Socket   |
| Contact Type                    | Right angle solder   |
| Contact Material                | copper alloy   |
| Contact Finish                  | Gold flash (4-10 microinch) over 100 microinch nickel  |
| Hardware                        | 90° Metal Bracket, 4-40 Fastener, 4-40 Screwlock, Boardlock  |
| Disclaimer                      | Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML. |