



Products

Applications

Case Studies

About Us

Where to Buy

Investor Relations

News & Events

Contact Us

Request more info

Part Number: 5532212100F



5532212100F

Check Stock



RoHS Compliant Product
To learn more click here

General Description

Series 553
Configuration 3 mm Lens
Description 3 mm Bi-Level CBI
Package Options Bulk Packaging
Sizes 3mm

Lamp TypeBi-Level HousingViewingRight AnglePolarityCathode RightLens StyleTinted, Non-Diffused

Viewing Angle 45
LED Centerline 2.54mm

Absolute Maximum Ratings (Ta = 25°)

Solder Temperature 260 for 5 secs Operating Temperature -55 to +100 Storage Temperature -55 to +100

Operating Characteristics

Color	Red	Green
LED Type	High Efficiency	High Efficiency
Peak Wave Length	635	565
LED Position	1	2
Luminous Intensity Min	8.7	32
Luminous Intensity Typical	29	50
Forward Voltage Typical	2	2.1
Forward Voltage Max	2.8	2.8
Test Current mA	10mA	
Backlighting	Yes	
Pitch Between Vertical	5.08	
Power Dissipation Max	100mW	100mW





Privacy and Cookies Policy

Terms and Conditions

Dialight BTI









