



- [Circuit Board Indicators](#)
- [Panel Mount Indicators](#)
- [Solid State Lighting](#)
- [Traffic Signals](#)
- [Vehicle Lighting](#)
- [Rail](#)
- [Obstruction Lighting](#)
- [Hazardous Area Lighting](#)
- [Heliport Lighting](#)

Circuit Board Indicators - Through Hole Indicators

P/N# 5680122233F	Rectangle Lens	
Description	2X4 mm Quad-Level CBI G-G-Y-Y	
Package Options	5 Pieces Per Bag	
Product Type	Through Hole Indicators	
Sub Product Type	with Quad Level Housing	
Configuration	Rectangle Lens	
Viewing	Right Angle	
Viewing Angle	104	
Test Current (mA)	10mA	

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp	260Å° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C

Distributor Stock Check

Check stock with our distributors now.

5680122233F

[check stock](#)



Operating Characteristics

LED Position	Found in position(s): 1,2	Found in position(s): 3,4
Color		
Lamp Type	Single Color	Single Color
LED Type	High Efficiency	High Efficiency
Intensity Min (mcd)	0.0	0.0
Intensity Typ (mcd)		
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)	588	588
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)	100	60
Backlighting		
Pitch Between Vertical		
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

- how to purchase*
- [sales contacts](#)
 - [stock check](#)

search

[Product Line Search](#)

Please select a Product Line to search.

[find](#)

Part # / Text Search

Part No.:

Text Search:

[search](#)

[quick links](#)

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes

[FAQs](#)

Dialight Ltd (UK)

[Dialight Garufo](#)

[Dialight BLP](#)

[LumiDrives](#)