



Product Navigation

**Circuit Board Indicators**

**Panel Mount Indicators**

**Solid State Lighting**

**Traffic Signals**

**Vehicle Lighting**

**Rail**

**Obstruction Lighting**

**Hazardous Area Lighting**

**Heliport Lighting**

how to purchase

sales contacts

stock check

search

Product Line Search

Please select a Product Line to search.

Circuit Board Indicators

find

Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes  
FAQs


Dialight Ltd (UK)  
Dialight Garufo  
Dialight BLP  
LumiDrives

**Circuit Board Indicators - Through Hole Indicators**

P/N# <b>5682234323F</b>	3 mm Lens
Description	3 mm Quad-Level CBI Y/G-Y-G-Y
Package Options	5 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Quad Level Housing
Configuration	3 mm Lens
Viewing	Right Angle
Viewing Angle	80
Test Current (mA)	10mA

**Absolute Maximum Ratings (Ta = 25 °)**

Solder Temp	260Å° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C



**Distributor Stock Check**

Check stock with our distributors now.

5682234323F

[check stock](#)

**Operating Characteristics**

	Found in position(s): 1	Found in position(s): 2,4	Found in position(s): 3
LED Position			
Color	Yellow / Green	Yellow	Green
Lamp Type	Bi-Color / Bi-Color	Bi-Color	Bi-Color
LED Type			
Intensity Min (mcd)	2.5 / 2.5	10.0	32.0
Intensity Typ (mcd)	4.3 / 6.3		50.0
Intensity Max (mcd)		50	
Fwd Voltage Min			
Fwd Voltage Typ			
Fwd Voltage Max			
Dom Wavelength Min (nm)	587 / 569	587	569
Dom Wavelength Typ (nm)			
Dom Wavelength Max (nm)			
Power Dissipation Max (mW)	60 / 100	60	100
Backlighting			
Pitch Between Vertical			
Pitch Between Horizontal			
Lum Intensity Min			
Lum Intensity Typ			
Lum Intensity Max			