



 Dialight - Leader in LED Technology



- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	PLCC-2 Single Color
5973901207F	
Description	


Region:
 Product Line:

Reverse Current	10 @ Vr =5V
Forward Current Continuous	20 mA
Derating	from 75Â° @ .6mA/Â°C
Reverse Voltage	5 V
Operating Temp	-40~+100° C
Storage Temp	-40~+100° C

Distributor Stock Check


Check stock with our distributors now.






Check stock with our distributors now.

 RoHS Compliant Product




Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Operating Characteristics	
LED Position	
Color	White
Lamp Type	Single Color
LED Type	InGaN
Intensity Min (mcd)	90
Intensity Typ (mcd)	180.0
Intensity Max (mcd)	
Fwd Voltage Min	3.5
Fwd Voltage Typ	4.2
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	85
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	





 Please select a Product Line to search.



Part No.:

 Text Search:

Copyright 2006 Dialight. All rights reserved | [Privacy Policy](#)

[Dialight Corporate Video](#)

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp.
[View PDF File](#)

[Application Notes](#)
[FAQs](#)

[Dialight Ltd \(UK\)](#)
[Dialight Garufo](#)
[Dialight BLP](#)
[LumiDrives](#)

menu rendered