



- ? [Circuit Board Indicators](#)
- ? [Panel Mount Indicators](#)
- ? [Solid State Lighting](#)
- ? [Traffic Signals](#)
- ? [Vehicle Lighting](#)
- ? [Rail](#)
- ? [Obstruction Lighting](#)
- ? [Hazardous Area Lighting](#)
- ? [Heliport Lighting](#)

Circuit Board Indicators - Surface Mount Indicators	
P/N#	1210 Package Bi - Color
5977702602F	
Description	

Region:

Product Line:

Circuit Board Indicators

Solder Temp	260Å° fo 5 sec
Operating Temp	-55~+100° C
Storage Temp	-55~+100° C

Distributor Stock Check

Check stock with our distributors now.

5977702602F



Check stock with our distributors now.

5977702602F

Please note that the stock check **is only applicable** to products *within* **Circuit Board Indicators** and **Panel Mount Indicators**.

Please select a Product Line to search.

Circuit Board Indicators

Operating Characteristics	
LED Position	
Color	Red / Green
Lamp Type	Bi-Color / Bi-Color
LED Type	
Intensity Min (mcd)	3.6 / 9.0
Intensity Typ (mcd)	6.3 / 16.0
Intensity Max (mcd)	9 / 23
Fwd Voltage Min	2.0 / 2.2
Fwd Voltage Typ	2.8 / 2.8
Fwd Voltage Max	
Dom Wavelength Min (nm)	653 / 575
Dom Wavelength Typ (nm)	100 / 100
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Part No.:

Text Search: