

Note1. Applicable wire size: AWG#24~28  
(Outside diameter:  $\phi$ 1.0~1.5mm)

Note2. Applicable insulator  
 HKP- (2~50) FSA01  
 HKP- (4~70) FA01  
 Case of F504 or F514  
 HKP- (2~20) FSA01  
 HKP- (4~20) FA01

Note3. Applicable extracting tool  
 HKP-RF




Table 1

Part number	Type of Terminal	Plating		Applicable crimping tool
		Contact area	Other area	
HKP-F503A	Strip Form Terminal	Gold 0.8 $\mu$ m	Nickel 1 $\mu$ m	Automatic Crimping Machine Machine Body : HTK-512 Applicator : KP-214
HKP-F503B		Gold 0.3 $\mu$ m	Nickel 1 $\mu$ m	
HKP-F504		Tin $\Delta$		
HKP-F603B	Loose Piece Terminal	Gold 0.3 $\mu$ m	Gold 0.05 $\mu$ m	Manual Crimping Tool : KP-325
HKP-F513A		Gold 0.8 $\mu$ m	Nickel 1 $\mu$ m	
HKP-F513B		Gold 0.3 $\mu$ m	Nickel 1 $\mu$ m	
HKP-F514		Tin $\Delta$		
HKP-F613B		Gold 0.3 $\mu$ m	Gold 0.05 $\mu$ m	

$\Delta$								
$\Delta$								
$\Delta$	070710	S. Iijima	Dim., e. t. c		Female contacts	Phosphor Bronze	See table1	—

LTR.	DATE	BY	REV.	DESCRIPT	No.	PART NAME	MATERIAL	QTY	FINISH	NOTE
------	------	----	------	----------	-----	-----------	----------	-----	--------	------

DATE May.09 (2005)		SCALE 5/1		UNIT mm (INCH)		3RD. A. P		HONDA TSUSHIN KOGYO CO., LTD.			
APP. DATE & REV.		DR.		DE.		CHK.		CHK.		APP.	
		S. IIJIMA		S. IIJIMA		—		C. NUNOKAWA		K. KASHIO	
		NAME		Female contacts (RoHS) $\Delta$		PART NO.		HKP-F503A, B•504•603B F513A, B•514•613B		REV. 1A	