

Straight through hole type male connector for PCB
PCR-()MD()+

For PCB

Straight Through hole

RoHS



● Configuration of product Part No.

PCR- () MD ()+

① ② ③ ④

- ① Series name
- ② No. of contacts: 20, 34, 48, 68, 80, 96 or 128
- ③ Type of connector
MD: Straight through hole type, male
- ④ Board lock
K: With kink-formed contacts

for 20, 48, 68, 80, 96 or 128-contact connectors.

Recommended PCB layout

4 kink-formed contacts

POS.#1 Reference pin

for 20, 48, 68, 80, 96 or 128-contact connectors.

● Components

①	Insulator
②	Male contacts

● Dimensions

Part No.	A	B	C	D
PCR-20MD()+	22.74	13.14	11.43	18.14
PCR-34MD()+	31.63	22.03	20.32	27.03
PCR-48MD()+	40.52	30.92	29.21	35.92
PCR-68MD()+	53.22	43.62	41.91	48.62
* PCR-80MD()+	60.84	51.24	49.53	56.24
PCR-96MD()+	71.00	61.40	59.69	66.40
PCR-128MD()+	91.32	81.72	80.01	86.72

*Note: These products are under consideration.

Mating connectors: PCR-()FD()+, PCR-()LFD()+