



| No. of Contacts n | A | B |
|----------------------|-------|-------|
| 1 | — | 2.54 |
| 2 | 2.54 | 5.08 |
| 3 | 5.08 | 7.62 |
| 4 | 7.62 | 10.16 |
| 5 | 10.16 | 12.7 |
| 6 | 12.7 | 15.24 |
| 7 | 15.24 | 17.78 |
| 8 | 17.78 | 20.32 |
| 9 | 20.32 | 22.86 |
| 10 | 22.86 | 25.4 |
| 11 | 25.4 | 27.94 |
| 12 | 27.94 | 30.48 |
| 13 | 30.48 | 33.02 |
| 14 | 33.02 | 35.56 |
| 15 | 35.56 | 38.1 |
| 16 | 38.1 | 40.64 |
| 17 | 40.64 | 43.18 |
| 18 | 43.18 | 45.72 |
| 19 | 45.72 | 48.26 |
| 20 | 48.26 | 50.8 |
| 21 | 50.8 | 53.34 |
| 22 | 53.34 | 55.88 |
| 23 | 55.88 | 58.42 |
| 24 | 58.42 | 60.96 |

NOTE 1.

| PART NO. | Contact Plating |
|-------------------|---------------------------------|
| Z-149- (n) P | 0.7 μ m Gold (Contact Area) |
| (DIC-149- (n) P) | Over Nickel |
| Z-149A- (n) P | 0.4 μ m Gold (Contact Area) |
| (DIC-149A- (n) P) | Over Nickel |

| | | | | | | | | |
|-------------|--|--|---|-----------|---------|---|--------|------------------|
| \triangle | | | | | | | | |
| \triangle | | | 2 | Contact | Brass | n | NOTE1. | — |
| \triangle | | | 1 | Insulator | 66Nylon | 1 | — | UL94V-0 Black |

| LTR. | DATE | BY | REV. | DESCRIPT | No. | PART NAME | MATERIAL | QTY | FINISH | NOTE |
|------|------|----|------|----------|-----|-----------|----------|-----|--------|------|
|------|------|----|------|----------|-----|-----------|----------|-----|--------|------|

| | | | | | | | | | | |
|--------------|-------|-----------|-----------|-------------------------------|--|--|--|--|--|--|
| DATE | SCALE | UNIT | 3RD. A. P | HONDA TSUSHIN KOGYO CO., LTD. | | | | | | |
| OCT. 3. 1997 | 2 / 1 | mm (INCH) | | | | | | | | |

| DR. | DE. | CHK. | CHK. | APP. | NAME | MALE CONNECTOR |
|-------------|-------------|-------------|------------|--------------|----------|---|
| M. KASAHARA | M. KASAHARA | C. NUNOKAWA | H. EBIHARA | M. TAKAHASHI | PART NO. | Z-149 () - (n) P (DIC-149 () - (n) P) |