

4AC8

(Home : Products : Sw itches : MICRO SWITCH™ Basic Sw itches : Standard Miniature and Subminiature Sw itches : AC)



AC Series Door Switch, Single Pole Double Throw Double Break Circuitry, 15 A at 250 Vac, Steel Rod Actuator, Screw Termination

[click here to download Hi-Res image](#)

Actual product appearance may vary.

Product Specifications

Sw itch Type	Door 38,1 mm H x 12,7 mm W x 38,1 mm L [1.5 in H x 0.5 in W x 1.5 in L]
Sealed	No
Ampere Rating	15 A
Circuitry	SPDT, DB (2 CKT DB)
Actuator	Rod
Termination	Screw
Operating Temperature	-55 °C to 85 °C [-67 °F to 185 °F]
Voltage	250 Vac
Contact Type	Silver
Operating Position (OP)	4,75 mm [0.187 in] min.
Free Position (FP)	9,53 mm [0.375 in] max.
Housing Material	Stainless Steel Bracket, Stainless Steel Rod
Package Height	66,55 mm [2.62 in]
Package Width	13,2 mm [0.52 in]
Package Length	40,39 mm [1.59 in]
Availability	Global
UNSPSC Code	39122209
UNSPSC Commodity	39122209 Snap sw itches
Series Name	AC