



# RM502012 Product Details

[Share](#) | [Print](#) | [Email](#)


**RM502012**  
(7-1393148-8)

TE Internal Number: 7-1393148-8

Active

## Industrial Relays (General Purpose)

Converted to EU RoHS but not ELV Compliant (Find RoHS Compliant Alternates/Statement of Compliance)

### Product Highlights:

- RM 5/6/B Series
- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- Contact - Rated Current = 16 A
- Terminal Type = Plug-in, Quick Connect
- Contact - Arrangement = 2 Form A (NO)

[View all Features](#)

### Quick Links

- ▶ Pricing & Availability
- ▶ Search for Tooling
- ▶ Product Feature Selector
- ▶ Contact Us About This Product

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

## Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

- Additional Information:**
- [Product Line Information](#)
- Related Products:**
- [Tooling](#)

## Product Features (Please use the Product Drawing for all design activity)

**Electrical Characteristics:**

- Contact - Current Class = 10A to 20A Class, Greater Than 16A
- [Contact - Rated Current \(A\)](#) = 16
- Contact - Limiting Continuous Current (A) = 16
- Contact - Limiting Making Current (A) = 30
- Contact - Limiting Breaking Current (A) = 16
- Insulation - Initial Dielectric Between Coil/Contact Class = 1500V to 2500VA Class
- Insulation - Initial Dielectric Between Open Contacts (V rms) = 2500
- Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 2500
- Contact - Rated Voltage (VAC) = 400
- Contact - Switching Voltage Max. (VAC) = 440
- Contact - Limiting Short-Time Current (A) = 16
- Contact - Switching Recommended Load, Min. = 100mA at 24V
- Coil - Rated Voltage (VDC) = 12
- [Coil - Resistance \(Ω\)](#) = 86
- [Coil - Rated Power, DC \(mW\)](#) = 1700
- Coil - Rated Power Class = >1.5W Class
- Insulation - Initial Dielectric Between Adjacent Contacts (V rms) = 2500
- Insulation - Creepage Class = >8mm Class
- Insulation - Clearance Class = 2.5mm to 4mm Class
- Insulation - Special Features = 5000V Initial Surge Withstand Voltage between Contacts and Coil

**Dimensions:**

- Mechanical - Length Class = 35mm to 40mm Class
- Length (mm [in]) = 38.50 [1.515]
- Mechanical - Width Class = 30mm to 40mm Class
- Width (mm [in]) = 35.50 [1.398]
- Mechanical - Height Class = 40mm to 50mm Class
- Height (mm [in]) = 48.50 [1.909]
- Insulation - Clearance Between Contact and Coil (mm [in]) = 4 [0.157]
- Insulation - Creepage Between Contact and Coil (mm [in]) = 14.9 [0.587]

**Body Features:**

- Mount Type = Socket
- Weight (g [oz]) = 81.00 [2.859]

**Contact Features:**

- Terminal Type = Plug-in, Quick Connect
- Contact Material = AgCdO
- Contact - Number of Poles = 2
- Contact - Special Features = 3mm Contact Gap

**Configuration Features:**

- [Contact - Arrangement](#) = 2 Form A (NO)
- [Coil - Magnetic System](#) = Monostable, DC
- Coil - Special Features = UL Coil Insulation Class B

**Industry Standards:**

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Converted to comply with RoHS not ELV directives
- Approved/Registered Standards = cULus, VDE

**Environmental:**

- Environmental - Category of Protection = RTI
- Environmental - Ambient Temperature, Max. (°C [°F]) = 50 [122]
- Environmental - Ambient Temperature Class = 0 to 50°C Class

**Packaging Features:**

- Packaging Method = Tray

**Other:**

- Series = RM 5/6/B
- Brand = Schrack
- Accessories/Socket Type = PCB Socket, DIN-rail Socket, Panel Socket

Feedback

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility](#)

[Plan](#)

[Product Cross Reference](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Find a Phone Number](#)

[Knowledge Base](#)

[Manage Your Account](#)

