





FFMD-20-T-02.00-01-N-R



FFMD-10-S-10.00-01



**FFMD SERIES**

**(1.27 mm) .050"**

# TIGER EYE™ FLAT IDC WIRE CABLES

**Mates with:**  
 FLE\*, SFMC\*,  
**Transfer End Option**  
**Mates with:** FTS, FTSH,  
 EHF, SHF, ESHF

## SPECIFICATIONS

For complete specifications see [www.samtec.com?FFMD](http://www.samtec.com?FFMD)

**Insulator Material:**  
 Black Glass Filled Polyester

**Terminal:**  
 Phosphor Bronze

**Contact:**  
 BeCu (-T)

**Plating:**  
 Sn over 50 μ" (1.27 μm) Ni

**Wire:** 30 AWG

**Current Rating:**  
 2.5 A per pin  
 (1 pin powered)

**Operating Temp Range:**  
 -40 °C to +105 °C

**Voltage Rating:**  
 215 VAC  
 304 VDC

**RoHS Compliant:**  
 Yes

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)




FILE NO. E111594

## ALSO AVAILABLE (MOQ Required)

- Other sizes
- Contact Samtec.

**\*Note:** Standard FFMD callout will not mate with FLE, SFMC. Must use gold plated callouts. (See drawing on web.)  
 When mated with a socket, Wire 1 mates with Pin 2; Wire 2 mates with Pin 1, etc.

**Note:** This Series is non-standard, non-returnable.



## FFMD = Terminal Strip

