





- Fully Insulated
- Metal Insulation Sleeve
- Molded Insulator
- Internal Barrel Serrations
- Funnel Entry



- Brazed Seam
- Internal Barrel Serrations
- Funnel Entry



### Nylon Fully Insulated Bullet Receptacles



Catalog Number	Wire Range	Dimension <small>inch mm</small>					
		W	F	L	B	D	T
KNF18-4FB-M	22-16 A.W.G. 0.5-1.5 mm <sup>2</sup>	.153 3.9	.287 7.3	.992 25.2	.433 11.0	.157 4.0	.016 0.4
	16-14 A.W.G. 1.5-2.5 mm <sup>2</sup>	.153 3.9	.287 7.3	.992 25.2	.433 11.0	.197 5.0	.016 0.4

Box Quantity: (M)=1000

For Mylar Tape replace box quantity with (T). Example: KNF18-4FB-T  
UL File #E66716

See pages in back of catalog for complete tool information.  
Tool and Die Selection Chart on page 40.

**Maximum Electrical Rating:** 105°C 600 Volts Max.  
**Terminal Material:** Brass with Copper Sleeve

### Vinyl Fully Insulated Bullet Receptacles



Catalog Number	Wire Range	Dimension <small>inch mm</small>					
		W	F	L	B	D	T
KVF18-4FB-M	22-16 A.W.G. 0.5-1.5 mm <sup>2</sup>	.153 3.9	.287 7.3	.917 23.3	.413 10.5	.150 3.8	.016 0.4
	16-14 A.W.G. 1.5-2.5 mm <sup>2</sup>	.153 3.9	.287 7.3	.917 23.3	.413 10.5	.185 4.7	.016 0.4
KVF10-5FB-D*	12-10 A.W.G. 4-6 mm <sup>2</sup>	.193 4.9	.276 7.0	.988 25.1	.492 12.5	.244 6.2	.018 0.45

\*Not UL listed

Box Quantity: (D)=500; (M)=1000

For Mylar Tape replace box quantity with (T). Example: KVF18-4FB-T  
UL File #E66716

See pages in back of catalog for complete tool information.  
Tool and Die Selection Chart on page 40.

**Maximum Electrical Rating:** 75°C 300 Volts Max.  
**Terminal Material:** Brass with Copper Sleeve