


# Sta-Kon®

## Locking Fork Terminals



Stock thickness same as ring terminal of same size.

### Vinyl Insulated Locking Fork—Insulation Support



| Cat. No.  | Bulk. Cat. No. | Pkg. Qty. | Wire Range | Max. Ins. | Wt./lbs. Bolt Hole | Per 1000 | Dimensions |     |     |     |
|-----------|----------------|-----------|------------|-----------|--------------------|----------|------------|-----|-----|-----|
|           |                |           |            |           |                    |          | A          | B   | C   | M   |
| 18RA-6FL  | RA2217         | 100/1M    | 22-16      | .150      | #6                 | 5        | .97        | .25 | .25 | .81 |
| —         | RA2227         | 1000      | 22-16      | .155      | #6                 | 5        | .97        | .29 | —   | .81 |
| 18RA-8FL  | RA2247         | 100/1M    | 22-16      | .150      | #8                 | 5        | .97        | .29 | .25 | .81 |
| 18RA-10FL | RA2257         | 100/1M    | 22-16      | .150      | #10                | 5        | .97        | .29 | .25 | .81 |
| 14RB-6FL  | RB2207         | 100/1M    | 18-14      | .170      | #6                 | 6        | .97        | .25 | .27 | .81 |
| —         | RB2217         | 1000      | —          | .170      | #6                 | 6        | .97        | .29 | .27 | .81 |
| 14RB-8FL  | RB2237         | 100/1M    | 18-14      | .170      | #8                 | 6        | .97        | .29 | .27 | .81 |
| 14RB-10FL | RB2257         | 100/1M    | 18-14      | .170      | #10                | 6        | .97        | .29 | .27 | .81 |
| 10RC-6FL  | RC2207         | 50/500    | 12-10      | .220      | #6                 | 8        | 1.09       | .31 | .27 | .90 |
| 10RC-8FL  | RC2217         | 50/500    | 12-10      | .220      | #8                 | 8        | 1.09       | .37 | .27 | .90 |
| 10RC-10FL | RC2227         | 50/500    | 12-10      | .220      | #10                | 8        | 1.09       | .37 | .27 | .90 |
| 10RC-14FL | RC2237         | 50/500    | 12-10      | .220      | 1/4"               | 8        | 1.09       | .49 | .27 | .90 |

U.L. Listed E-9809

Installing tools: ERG-2001, ERG-2003, WT145C, WT2000, WT112M

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.