

# F-14X

### Electrical Specifications (@25C)

1. Maximum Power: 7.56 VA
2. Primary: 115V 60 Hz
3. Secondary: 6.3VCT @ 1.2 Amps
4. Voltage Regulation: 15 % TYP @ full load to no load
5. Temperature Rise: 35C TYP (45C MAX allowed)

### Description:

The F-14X is part of a series which has a long history of reliable service in the field, made from a proven design and constructed with UL recognized materials.

### Construction:

Wound on a single channel nylon bobbin. Materials are UL recognized, Class B (130° C) rated.

### Safety:

These products are 100% hipot tested with an insulation of 2500V between primary and secondary windings as well as between the primary / secondary windings and the core.

### Dimensions: Units: In inches

A	B	C	D
1.625	2.812	1.625	2.375


Mounting Hole Diameter: .187 in

Lead length: 7.0 inches ± 1 inch

Weight: 0.70 lbs

Wire Gauge: 22AWG

### Schematic:



Primary: Black to Black  
Secondary: Green to Green

**RoHS Compliance:** As of manufacturing date February 2016, all standard products meet the requirements of 2015/863/EU, known as the RoHS 3 initiative.

\* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

